Compact Track Loaders / T630 Compact Track Loader Specifications & Options

Standard Optional N/A Not Applicable	Bobcat T630	
⊖ Engine	Standard	Roller Suspension Option
Emissions Tier (EPA)	iT 4	iT 4
Engine Cooling	Liqu	iid
Engine Fuel	Dies	sel
Horsepower	52,4	kW
Turbocharged Engine]

\bigcirc Performance

Rated Operating Capacity (SAE)	1012 kg	953 kg
Operating Capacity (50% of Tip)	1361 kg	1361 kg
Tipping Load	2722 kg	2722 kg
Operating Weight	4050 kg	4222 kg
Travel Speed	10.6 km/h	10.6 km/h
Travel Speed (2-speed option)	17.2 km/h	17.2 km/h
Ground Pressure (Rubber)	0.38 bar	0.39 bar

${\hfill \ominus}$ Capacities

Fuel Tank	166.4 I	166.4
-----------	---------	-------

\ominus Hydraulic System

System Relief @ Quick Couplers	241,5 bar
Auxiliary Std Flow	87,1 l/min
Auxiliary High Flow	115,5 I/min

\bigcirc Dimansion

Length	2753 mm	
Length without Attachment	2753 mm	
Length with Standard Bucket	3474 mm	
Width	1851 mm	1941 mm
Width (with bucket)	1880 mm	2032 mm
Height	2065 mm	
Height with Operator Cab	2065 mm	
Height to Bucket Hinge Pin	3073 mm	
Reach @ Maximum Height	613 mm	
Turning Radius	2238 mm	2238 mm
Length of track on ground	1486 mm	
Track Width	320 mm	
Track Width - Optional	450 mm	

\bigcirc Features

Joystick Control	
Air Conditioning	\checkmark
Backup Alarm	
BICS System (Interlock)	
Cab Heater	\checkmark
Operating Lights	
Suspension Seat	
Two Speed Travel	\checkmark
Deluxe Instrumentation	\checkmark
Engine Shutdown	
Hydraulic Bucket Positioning	\checkmark
High Flow Option	
Auxiliary Hydraulics	
Bob-Tach Attachment System	
Power Bob-Tach	
ACS (Switchable Controls)	\checkmark
Ride Control	\checkmark
Horn	

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.