Standard Optional N/A Not Applicable	Bobcat T650		
Engine	Standard	Roller Suspension Option	
Emissions Tier (EPA)	iT4	iT4	
Engine Cooling	Liquid		
Engine Fuel		Diesel	
Horsepower	5	52,4 kW	
Turbocharged Engine		✓	
→ Performance			
Rated Operating Capacity (SAE)	1166 kg	1166 kg	
Operating Capacity (50% of Tip)	1665 kg	1665 kg	
Tipping Load	3331 kg	3331 kg	
Operating Weight	4281 kg	4542 kg	
Travel Speed	10.6 km/h	10.6 km/h	
Travel Speed (2-speed option)	17.2 km/h	17.2 km/h	
Ground Pressure (Rubber)	0.40 bar	0.42 bar	
─ Capacities			
Fuel Tank	166.2	166.2	
System Relief @ Quick Couplers	2.	41,5 bar	
Auxiliary Std Flow		7,1 I/min	
Auxiliary High Flow		115,5 I/min	
→ Dimansion			
Length	3	475 mm	
Length without Attachment	2	753 mm	
Length with Standard Bucket	3	475 mm	
Width	1851 mm	1941 mm	
Width (with bucket)	1880 mm	2032 mm	
Height	20	065 mm	
Height with Operator Cab	20	065 mm	
Height to Bucket Hinge Pin	3	149 mm	
Reach @ Maximum Height	3	370 mm	
Turning Radius	2228 mm	2228 mm	
Length of track on ground	14	486 mm	
Track Width	3	320 mm	
Track Width - Optional	4	150 mm	
∃ Features			
Joystick Control		✓	
Air Conditioning		✓	
Backup Alarm			
BICS System (Interlock)			
Cab Heater		✓	
Operating Lights			
Suspension Seat			
Two Speed Travel		✓	
Deluxe Instrumentation		✓	
Engine Shutdown			

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.

Hydraulic Bucket Positioning

Bob-Tach Attachment System

ACS (Switchable Controls)

High Flow Option

Power Bob-Tach

Ride Control

Horn

Auxiliary Hydraulics

~

 \checkmark

V

 \checkmark

V