

Compact Track Loaders / T870 Compact Track Loader

Specifications & Options

■ Standard
 Optional
N/A Not Applicable

Bobcat T870

⊖ Engine

Emissions Tier (EPA)	Tier 3
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	72,9 kW
Turbocharged Engine	<input checked="" type="checkbox"/>

⊖ Performance

Rated Operating Capacity (SAE)	1599 kg
Operating Capacity (50% of Tip)	2282 kg
Tipping Load	4569 kg
Operating Weight	5751 kg
Travel Speed	11.6 km/h
Travel Speed (2-speed option)	18.3 km/h
Ground Pressure (Rubber)	0.33 bar

⊖ Capacities

Fuel Tank	122.3 l
------------------	---------

⊖ Hydraulic System

System Relief @ Quick Couplers	241,5 bar
Auxiliary Std Flow	89,3 l/min
Auxiliary High Flow	141,6 l/min

⊖ Dimansion

Length	3909 mm
Length without Attachment	3030 mm
Length with Standard Bucket	3909 mm
Width	2108 mm
Width (with bucket)	2153 mm
Height	2118 mm
Height with Operator Cab	2118 mm
Height to Bucket Hinge Pin	3657 mm
Reach @ Maximum Height	927 mm
Turning Radius	2514 mm
Length of track on ground	1749 mm
Track Width	450 mm

⊖ Features

Joystick Control	<input checked="" type="checkbox"/>
Air Conditioning	<input checked="" type="checkbox"/>
Backup Alarm	<input type="checkbox"/>
BICS System (Interlock)	<input type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>
Operating Lights	<input type="checkbox"/>
Suspension Seat	<input type="checkbox"/>
Two Speed Travel	<input checked="" type="checkbox"/>
Deluxe Instrumentation	<input checked="" type="checkbox"/>
Engine Shutdown	<input type="checkbox"/>
Hydraulic Bucket Positioning	<input checked="" type="checkbox"/>
High Flow Option	<input checked="" type="checkbox"/>
Auxiliary Hydraulics	<input type="checkbox"/>
Bob-Tach Attachment System	<input type="checkbox"/>
Power Bob-Tach	<input checked="" type="checkbox"/>
ACS (Switchable Controls)	N/A
Ride Control	<input checked="" type="checkbox"/>
Horn	<input type="checkbox"/>

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.