



Breaker, Breaker, Breaker, Breaker, Breaker,
Nail Point - Nail Point - Nail Point - Nail Point - Nail Point
HB280 HB680 HB880 HB980 - HB1180

General

Operating Weight	58 kg	127 kg	194 kg	228 kg	299 kg
Length	866 mm	1036 mm	1189 mm	1270 mm	1389 mm
Width	201 mm	279 mm	320 mm	320 mm	442 mm
Height	249 mm	401 mm	450 mm	450 mm	505 mm
Blows per minute	1290	1340	1310	1450	1280
Blows per minute Flow	22.7 l/ min	49.2 l/ min	64.4 l/ min	79.5 l/ min	98.4 l/ min
Impact Energy Class	60 ft.- lb. (81 J)	150 ft.- lb. (200 J)	300 ft.- lb. (407 J)	500 ft. lb. (650 J)	750 ft. lb. (1016 J)
Tool Diameter	38 mm	56 mm	66 mm	72 mm	76 mm



Breaker, Nail Point - HB1380

Breaker, Nail Point - HB2380

BOBCAT- BREAKER

General

Operating Weight	385 kg	410 kg	290 kg
Length	1488 mm	1588 mm	n/ a
Width	442 mm	442 mm	257 mm
Height	505 mm	505 mm	n/ a
Blows per minute	1230	910	n/ a
Blows per minute Flow	121.1 l/ min	124.9 l/ min	n/ a
Impact Energy Class	850 ft.- lb. (1152 J)	1000 ft.- lb (1356 J)	n/ a
Tool Diameter	86 mm	97 mm	n/ a

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.