

Skid-Steer Loaders / S570 Skid-Steer Loader

Specifications & Options

■ Standard
 Optional
N/A Not Applicable

Bobcat S570

⊖ Engine

Emissions Tier (EPA)	Interim Tier 4
Engine Cooling	Liquid
Engine Fuel	Diesel
Horsepower	45,5 kW
Turbocharged Engine	<input checked="" type="checkbox"/>

⊖ Performance

Rated Operating Capacity (SAE)	885 kg
Tipping Load	1769 kg
Operating Weight	2900 kg
Travel Speed	11.8 km/h
Travel Speed (2-speed option)	17.3 km/h

⊖ Capacities

Fuel Tank	93,7 l
------------------	--------

⊖ Hydraulic System

System Relief @ Quick Couplers	241,32 bar
Auxiliary Std Flow	64,7 l/min
Auxiliary High Flow	101,1 l/min

⊖ Dimansion

Length	3378 mm
Length without Attachment	2657 mm
Length with Standard Bucket	3378 mm
Width	1643 mm
Width (with bucket)	1727 mm
Height	1976 mm
Height with Operator Cab	1976 mm
Height to Bucket Hinge Pin	3023 mm
Reach @ Maximum Height	828 mm
Turning Radius	2024 mm
Wheelbase	1082 mm

⊖ Features

Joystick Control	<input checked="" type="checkbox"/>
Air Conditioning	<input checked="" type="checkbox"/>
Adjustable Seat	■
Backup Alarm	■
BICS System (Interlock)	■
Cab Enclosure	<input checked="" type="checkbox"/>
Sound Option	<input checked="" type="checkbox"/>
Cab Heater	<input checked="" type="checkbox"/>
Operating Lights	■
Parking Brake	■
Radio	<input checked="" type="checkbox"/>
Rear Window	■
Top Window	■
Lift-Arm Support	■
Seat Belt	■
Suspension Seat	<input checked="" type="checkbox"/>
Two Speed Travel	<input checked="" type="checkbox"/>
Deluxe Instrumentation	<input checked="" type="checkbox"/>
Engine Shutdown	■
Hydraulic Bucket Positioning	<input checked="" type="checkbox"/>
High Flow Option	<input checked="" type="checkbox"/>
Auxiliary Hydraulics	■
Spark Arrestor Muffler	■
Bob-Tach Attachment System	■
Power Bob-Tach	<input checked="" type="checkbox"/>
ACS (Switchable Controls)	<input checked="" type="checkbox"/>
Ride Control	<input checked="" type="checkbox"/>
Rear Hydraulics	<input checked="" type="checkbox"/>
Horn	■

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.